EAGTAC offers high performance tactical light instruments in EAGTAC and SPORTAC brands. We bring you the latest super bright LED technology, easy-to-use user interface with innovative features, cutting edge electronic circuitry, and trusted flashlight design at outstanding prices.

EAGTAC®

Product Catalog 2020

Offical Distributor:
HongDa Tech (HK) Limited
+852-8199-9604
hongda@eagtac.com

IWA Outdoor Classics 2020
Hall 5 : Stand 5-409

Visit us at: www.eagtac.com
Order E-mail: sales@eagtac.com

Disclaimer: All product specifications and features may be subject to change without notice.
All right reserved. EAGTAC LLC

DX3B Clicky Pro

Brightness	2500 lumen
LUX@1M	7200 lux
Runtime	0.4-75 hrs
Beam	185 yards
Battery	1 x 18350

- 18350 li-ion 1300mAh included, Tactical forward clicky switch
- CREE XHP50.2 LED, Built-in micro-USB 1A charger
- Battery level report, 2-way clip

D25C Clicky MKII

Brightness	800 lumen
LUX@1M	4100 lux
Runtime	0.6-1/300 hrs
Beam	140 yards
Battery	1xCR123A / 1xRCR123A

- All new A1650 RC circuit offering 70% more output than the original A950
- Programmable low and very low output
- Boost and buck circuit with moonlight and user-defined startup function

DX3L

Brightness	2500 lumen
LUX@1M	7200 lux
Runtime	0.7-1.1/190 hrs
Beam	185 yards
Battery	1 x 18650

- CREE XHP50.2 LED, Built-in micro-USB 1A charger, 18650 3400mah li-ion included
- Battery level report, stainless steel deep pocket clip, Tactical forward clicky switch

18650 li-ion battery

High discharge 3.7V w/ built-in 10A protection PCB

3500mAh
3400mAh
3600mAh
2600mAh

D25LC2 Clicky MKII

Brightness	1480 lumen
LUX@1M	10500 lux
Runtime	1.1-2.2/1200 hrs
Beam	223 yards
Battery	1x18650 / 2xCR123A

- All new C3600 RC circuit offering 80% more output than the original c2000
- Moonlight and programmable startup level
- Programmable low and very low output

D25A Clicky MKII

Brightness	405 lumen
LUX@1M	1200 lux
Runtime	1-150 hrs
Beam	76 yards
Battery	1 x AA

- All new A750 RC circuit offering 90% more output than the original A400 circuit
- Memory setting (remeber last output)
- li-ion compatible

D25A2 Clicky

Brightness	520 lumen
LUX@1M	3200 lux
Runtime	1.4-200 hrs
Beam	124 yards
Battery	2 x AA

18350 21700 CR123A 16340

1300mAh
5000mAh
1700mAh
750mAh

D25LC2 Tactical

Brightness	1374 lumen
LUX@1M	9500 lux
Runtime	1.5-200 hrs
Beam	213 yards
Battery	1x18650 / 2xCR123A

D25A2 Tactical

Brightness	538 lumen
LUX@1M	3300 lux
Runtime	1.5-100 hrs
Beam	125 yards
Battery	2 X AA

D25AAA

Brightness	155 lumen
LUX@1M	500 lux
Runtime	0.7-6 hrs
Beam	50 yards
Battery	1xAAA / 1x10440

- Magnetized tailcap, Three brightness levels
- UV output also available

DX30LC2 / DX30LC2-R

Brightness	1160 lumen
LUX@1M	20800 lux
Runtime	1.5-200 hrs
Beam	314 yards
Battery	1x18650 / 2xCR123A

- Side switch + forward clicky tailcap switch , Five brightness levels w/ battery level repot
- Built-in fast li-ion charger, battery included, Charge with standard 5V 1A USB power port
- Battery level discharge / charging report

DX30LC2-R Side LED

365nm UV
395nm UV
Red XP-E2
CREE XP-L HI
850nm/940nm IR Osram
Green XP-E2

Brightness	1160 lumen
LUX@1M	20800 lux
Runtime	1.5-200 hrs
Beam	314 yards
Battery	1x18650 / 2xCR123A

- Extremely compact dual LED output setup, Spot and floody output
- Also available in many LED combination

DX3B Mini Pro

Brightness	2480 lumen
LUX@1M	6800 lux
Runtime	0.25-20 hrs
Beam	180 yards
Battery	1x18350

- CREE XHP50.2 LED, Built-in micro-USB 1A charger
- 18350 li-ion included, Battery level report
- 18650 li-ion extension tube, 2-way clip, and tail-cap w/ magnet (pro)

D3C / D3A Titanium

CREE XM-L2 U4 LED

lumen	LUX@1M	Runtime	1x CR123A 1x RCR123A	(Beam)
800	4100	0.6-1 to 300 hrs		140 yards

- Brass LED heatsink
- Silk smooth thread

lumen	LUX@1M	Runtime	AA	(Beam)
405	1200	1 to 150 hrs		76 yards

P series

Compact design and high output. Comes with one inch flashlight head.

P25LC2

Brightness	1374 lumen
LUX@1M	11800 lux
Runtime	1.5-200 hrs
Beam	239 yards
Battery	2xCR123A / 1x18650

P25A2

Brightness	538 lumen
LUX@1M	4100 lux
Runtime	1.4-100 hrs
Beam	140 yards
Battery	2 x AA

P200LC2

Brightness	1286 lumen
LUX@1M	10100 lux
Runtime	1.5-80 hrs
Beam	220 yards
Battery	1x18650 / 2XCR123A

P200A2

Brightness	527 lumen
LUX@1M	3900 lux
Runtime	1.5-25 hrs
Beam	135 yards
Battery	2 X AA

*Diffuser design patent pending

PX30LC2-DR

Brightness	1160 lumen
LUX@1M	17500 lux
Runtime	1.5-200 hrs
Beam	288 yards
Battery	1x18650 / 2xCR123A

PX30LC2-R

Brightness	1160 lumen
LUX@1M	25100 lux
Runtime	1.5-200 hrs
Beam	345 yards
Battery	1x18650 / 2xCR123A

Comparison Table
EAGTAC flashlights

*Depending on LED installed
**Weight w/ batteries

Model	DX3BRC PRO	D25ARC MKII	D25LC2 MKII	D25C MKII	DX3L	DX3B-M Pro	D25A
LED lumen*	2500	405	1480	800	2500	2480	229
ANSI lumen*	1850	286	1100	560	1850	1830	162
Brightness levels / AUX	5 / 1	4 / 5	5 / 6	5 / 6	5 / 1	5 / 1	4 / 7
Beam distance* (yards/m)	185(170)	76(69)	223(205)	140(128)	185 (170)	180(165)	62(57)
Runtime (hours)	0.4/75	1/150	1.1-2.2/1200	0.6-1/300	0.7-1.1/190	0.25/20	1.3/150
Length (inch/mm)	3.9 (100)	3.4 (87)	4.5 (115)	2.9 (75)	5.1 (131)	3.4 (86)	3.4 (87)
Weight (o.z./gram)	3 (85)	0.85 (24)	1.7 (49)	1.0 (29)	3.8 (108)	2.6 (75)	0.85 (24)
Batteries	1 18350	1 AA	1 18650 2 CR123A	1 CR123A	1 18650	1 18350	1 AA

Model	D25A2	D25LC2 TAC	D25A2 TAC	D25AAA	D25LC2C	DX30LC2	DX30LC2-BR
LED lumen*	520	1374	538	155	331|120|45|240	1160	1160
ANSI lumen*	375	1042	378	91	261|95|37|190	905	911
Brightness levels / AUX	4 / 7	4 / 5	4 / 7	3 / 7	3 / 8	5 / 3	5 / 3
Beam distance* (yards/m)	124(113)	294(270)	125(114)	50(45)	66(61)	309(284)	314(288)
Runtime (hours)	1.4/200	1.5/200	1.5/100	0.7/6	1.8/10/200	1.5/200	1.5/200
Length (inch/mm)	5.7 (146)	4.8 (123)	6.2 (157)	2.7 (70)	4.7 (119)	5.0 (126)	5.2 (132)
Weight (o.z./gram)	1.9 (54)	2 (60)	2.4 (72)	0.4 (13)	1.7 (50)	2.0 (55)	2.3 (65)
Batteries	2 AA	1 18650 2 CR123A	2 AA	1 AAA	1 18650 2 CR123A	1 18650 2 CR123A	1 18650 2 CR123A

Model	DX30LC2-R	DX30LC2-SR	P200A2	P200LC2	P25A2	P25LC2	PX30LC2-DR	PX30LC2-R
LED lumen*	1160	1160	527	1286	538	1374	1160+600	1160
ANSI lumen*	905	905	378	1053	414	1065	930	950
Brightness levels / AUX	5 / 3	5 / 3	3	3	4 / 5	4 / 5	5	5 / 3
Beam distance* (yards/m)	314(288)	314(288)	135(124)	220(201)	140(128)	239(217)	288(264)	345(317)
Runtime (hours)	1.5/200	1.5/200	1.5/25	1.5/80	1.4/100	1.5/200	1.5/200	1.5/200
Length (inch/mm)	5.2 (132)	5.2 (132)	6.3 (160)	5.0 (126)	6.2 (157)	4.9 (123)	5.2 (132)	5.4 (137)
Weight (o.z./gram)	flashlight only 2.1 (60)	2.4 (67)	2.8 (84)	2.3 (66)	2.6 (77)	2.1 (64)	2.1 (60)	2.4 (70)
Batteries	1 18650 2 CR123A	1 18650 2 CR123A	2 AA	1 18650 2 CR123A	2 AA	1 18650 2 CR123A	1 18650 2 CR123A	1 18650 2 CR123A

Comparison Table
EAGTAC flashlights

*Depending on LED installed
**Weight w/ batteries

Model	NEW TX3V	NEW T25V	TX3G PRO MKII	T25LR MKII	TX3L PRO	T25C2 PRO MKII	TX3G Pro	TX25C	T200C2	T25C2 Pro	TX25C2	T25L-R	TX30C2	NEW G3V	G3L	GX30L2R PRO MKII
LED lumen*	3550	3200	3550	2200	3000	2100	3000	642	1277	2000	1350	2000	2000	3200	3200	2250
ANSI lumen*	2900	2600	2900	1760	2500	1700	2500	556	1045	1600	1105	1603	1603	2600	2600	1800
Brightness levels / AUX	5 / 3	3 / 4	5 / 3	3 / 1	5 / 3	3 / 4	5 / 3	5 / 1	3	4 / 4	3 / 7	3 / 1	5 / 3	3 / 4	3 / 4	5 / 3
Beam distance* (yards/m)	234(214)	234(214)	234(214)	347(318)	211(193)	331(304)	211(193)	261(239)	281(258)	317(291)	285(261)	317(291)	317(291)	269(247)	269(247)	399(366)
Runtime (hours)	0.7-1.0/200	1.8/200	1.1/200	1.2/25	0.9/200	0.8-1.3/170	1-1.4/300	1.5/100	1.5/6/80	1-1.3/200	1.8/150	1-1.3/70	1-1.3/200	1.8/200	0.6-1/135	2/300
Length (inch/mm)	5.6 (143)	6.1 (156)	5.4 (138)	5.9 (149)	5.4 (137)	5.7 (146)	5.4 (138)	3.4 (88)	5.6 (141)	5.7 (146)	4.7 (120)	5.9 (149)	5 (128)	6.4 (163)	6.2 (157)	8.6 (220)
Weight (o.z./gram)	6.5 (184)	6.6 (188)	6.9 (195)	6.3 (180)	6 (171)	4.6 (130)	6.9 (195)	1.9 (56)	4.4 (125)	4.6 (130)	3.4 (95)	4.6 (130)	3.9 (110)	7 (200)	6.6 (189)	9.9 (280)
Batteries	1 21700	1 21700	1 26650	1 18650	1 18650	1 18650	1 26650	1-2 CR123A	1 18650 2 CR123A	1-2 18650	1-2 18650 2-4 CR123A	1 18650 2 CR123A	1 18650 2 CR123A	1 21700	1 18650	2 18650

Model	GX30L2-R Pro	GX25A3	GX30A3-D	G25C2	GX30L2-DR	GX25L2	GX25L2T	NEW S25V	S25LR MKII	SX30L2R PRO MKII	SX30L3 Pro	SX30L3-R Pro	SX30L2-R Pro	SX30C2	S25L-R
LED lumen*	2000	1278	1330+1000	1351	1700+820	1397	1397	1200	2200	2650	4350	4850	2000	2000	2000
ANSI lumen*	1590	1048	980	1122	1250	1147	1147	960	1780	2140	3650	4100	1590	1618	1618
Brightness levels / AUX	5 / 3	3 / 7	5 / 3	4 / 7	5 / 3	4 / 7	4 / 7	3 / 4	3 / 1	5 / 3	5 / 3	5 / 3	5 / 3	5 / 3	3 / 1
Beam distance* (yards/m)	369(338)	311(284)	492(452)	323(295)	530(486)	337(308)	524(479)	724(664)	460(422)	574(526)	367(337)	393(361)	434(398)	453(416)	453(416)
Runtime (hours)	1.3-2.0/200	1.3/3/100	0.9/100	1.8/150	1.8/200	2/180	2/180	2-3/250	1.2/25	2.1/400	1.4/300	1.1-2.2/160	2.6-3.9/400	1-1.3/200	1-1.3/70
Length (inch/mm)	8.6 (220)	4.3 (109)	4.3 (109)	5.9 (150)	8.5 (215)	8.8 (224)	9.7 (247)	6.9 (175)	6.6 (168)	9.2 (235)	5.9 (150)	6.2 (159)	9.2 (235)	5.6 (143)	6.6 (168)
Weight (o.z./gram)	9.9 (280)	5.2 (148)	4.8 (137)	4.8 (138)	9.6 (270)	6.8 (195)	11.3 (320)	8.0 (226)	8.1 (229)	15.9 (450)	12.3 (350)	14.8 (420)	15.9 (450)	4.9 (138)	6.3 (179)
Batteries	2 18650	3 AA 3 14500	3 AA	1-2 18650 2-4 CR123A	2 18650 (included)	2 18650 (included)	2 18650 (included)	1 21700	1 18650	2 26650	3 18650 6 CR123A	3 18650	2 26650	1 18650 2 CR123A	1 18650

Model	SX30A4	SX25L3	SX25A6	SX30A6-D	S200C2	SX25L2T	SX30L2-DR	SX25L2	NEW MX30L2R	NEW MX30L2C-R	MX3T Pro	MX30L3-R	MX30L3-CR	MX30L4-C	M30LC2-C	M25C2T
LED lumen*	2000	3300	1494	1405+1040	1278	1494	1700+940	1494	4500	3100	4850	4625	6000	4800	1284	1180
ANSI lumen*	1618	2750	1201	1102	1048	1201	1247	1201	3780	2500	4100	3893	5018	4005	1017	980
Brightness levels / AUX	5 / 3	4 / 7	3 / 7	5 / 3	3	4 / 7	5 / 3	4 / 7	5 / 3	5 / 3	5 / 3	5 / 3	5 / 3	5 / 3	4 / 7	4 / 7
Beam distance* (yards/m)	453(416)	405(371)	433(396)	572(525)	431(396)	544(498)	622(570)	433(396)	536(492)	801(735)	536(492)	475(436)	437(401)	692(635)	422(386)	700(640)
Runtime (hours)	0.9-1.2/180	1.5/350	1.8/200	1.5/200	1.5/6/80	2.7/200	2.3/250	2.7/200	1.3-3.2/300	1.3-3.3/320	0.9-1.3/80	0.9-1.3/80	0.9-1.3/80	1.5/300	1.8/200	1/100
Length (inch/mm)	4.7 (121)	5.7 (144)	6.8 (173)	6.9 (173)	6.1 (155)	9.9 (252)	9.0 (230)	9.5 (240)	10 (254)	9.6 (224)	6.7 (172)	6.8 (172)	5.8 (147)	5.6 (143)	6 (153)	8.1 (206)
Weight (o.z./gram)	7.7 (220)	10.9 (309)	9.2 (260)	8.6 (244)	5.9 (167)	18.8 (535)*	14.8 (420)*	16.4 (465)*	26 (723)*	23 (649)*	17.3 (490)*	11.4 (323)	10.7 (302)	14.7 (418)	9.5 (269)	18.3 (520)
Batteries	4 AA	3 18650 6 CR123A	6 AA	6 AA	1 18650 2 CR123A	2 26650 (included)	2 26650 (included)	2 26650 (included)	2 32650 (included)	2 32650 (included)	3 18650 (included)	3 18650 (included)	3 18650 (included)	4 18650 8 CR123A	1-2 18650 2-4 CR123A	1-2 18650 2-4 CR123A

Comparison Table
EAGTAC flashlights

*Depending on LED installed
**Weight w/ batteries

Model	MX25L2-C	MX25L2	MX25L2T	MX30L3	M30LC2 Pro	M30L4XC
LED lumen*	3445	2850	2850	3300	2000	5136
ANSI lumen*	2606	2210	2210	2750	1600	4312
Brightness levels / AUX	4 / 7	4 / 7	4 / 7	5 / 3	3 / 4	5 / 3
Beam distance* (yards/m)	645(592)	523(479)	668(611)	553(506)	489(449)	309(283)
Runtime (hours)	1.3/200	1.3/200	1.3/200	1.5/350	1-1.3/200	1.5/300
Length (inch/mm)	9.1(232)	10.5(267)	11.5(293)	6.5 (165)	6.9 (176)	5.1 (130)
Weight (o.z./gram)	23.2 (659)*	25.7 (730)*	34.4 (976)*	13.5 (398)	8.7 (248)	13 (378)
Batteries	2 32650 (included)	2 32650 (included)	2 32650 (included)	3 18650 6 CR123A	1-2 18650	4 18650 8 CR123A

Model	MX30I3C	MX25L4	MX25L4T	DH10LC2	PH10LC2	ZP10L9
LED lumen*	3780	3640	2850	1120	1120	5200
ANSI lumen*	2815	2950	2210	720	820	4500
Brightness levels / AUX	5 / 3	4 / 7	4 / 7	5 / 1	5 / 1	5 / 1
Beam distance* (yards/m)	464(426)	564(518)	668(611)	73(67)	172(158)	705(644)
Runtime (hours)	1.5/350	1.8/300	1.5/200	1.5/200	1.5/200	2/800
Length (inch/mm)	5.3(135)	6.7(170)	7.87(200)	3.8 (97)	4.1 (105)	7.6 (192)
Weight (o.z./gram)	12.9 (367)*	17.3 (490)*	26.1 (740)*	1.4 (43)	1.7(51)	25.6 (710)
Batteries	3 18650 6 CR123A	4 18650 8 CR123A	4 18650 8 CR123A	1 18650 2 CR123A	1 18650 2 CR123A	9 18650 (Battery Pack)

T25LR MKII

Brightness	2200 lumen
LUX@1M	25300 lux
Runtime	0.8-1.2/25 hrs
Beam	347 yards
Battery	1 x 18650

- All new W2200 circuit offers 10% higher output than the previous W1900
- Four layers FR-4 PCB, seven large MLCC capacitors, molded power inductor
- Synchronous boots converter with ultra low resistance power mosfet
- High current tactical switch tailcap, Deep stainless steel pocket clip
- includes 10A higher discharge 18650 battery

T series

Compact tactical flashlight. Features a 1 1/4 inches flashlight head.

TX3V NEW!

Brightness	3550 lumen
LUX@1M	11500 lux
Runtime	0.7-1.0/200 hrs
Beam	234 yards
Battery	1 x 21700

- 3.7V 5000mAh 21700 rechargeable protected li-ion battery
- Charge with any 2A+ USB/PD port
- Charges cell phone or any other USB device (up to 2 Amp)
- Four large MLCC decouple capacitors for low ripple voltage output
- Includes Type-C USB to USB-A convertor
- (Optional) Type-C to Type-C / lightning / micro-usb cable

T25V NEW!

Brightness	3200 lumen
LUX@1M	10500 lux
Runtime	0.8-1.8/200 hrs
Beam	234 yards
Battery	1 x 21700

- 3200 LED lumen / 2600 ANSI FL-1 lumen, Charging and discharge battery level report
- 21700 5000mAh battery included, Deep stainless steel pocket clip, Type-C USB rechargeable

TX3G Pro MKII

Brightness	3550 lumen
LUX@1M	11500 lux
Runtime	0.7-1.1/200 hrs
Beam	234 yards
Battery	1 x 26650

- Type-C USB fast charging, Dual switch
- Five output levels, 26650 li-ion included

TX3L

Brightness	3000 lumen
LUX@1M	9350 lux
Runtime	0.5-0.7/150 hrs
Beam	211 yards
Battery	1 x 18650

- Type-C USB fast charging, Dual switch
- Five output levels, 18650 li-ion included

TX30C2

Brightness	2000 lumen
LUX@1M	21200 lux
Runtime	1.3/200 hrs
Beam	317 yards
Battery	1x18650 / 2xCR123A

- Five output leves, Dual switch operations
- Side signal switch w/ momentary on/off
- Extend runtime with two 18650 batteries

T200C2

Brightness	1277 lumen
LUX@1M	16600 lux
Runtime	1.5/80 hrs
Beam	281 yards
Battery	1x18650 / 2xCR123A

- Three output levels
- Tactical forward clicky swich

TX25C

Brightness	642 lumen
LUX@1M	14300 lux
Runtime	1.0/150 hrs
Beam	261 yards
Battery	1 x CR123A

- Five output levels, Instant MIN or MAX output
- Auto-adjust output current for single and two battery setup
- Extension battery tube for extended runtime and higher lumen output

T25C2 Pro MKII

Optional remote pressure switch

Brightness	2100 lumen
LUX@1M	23100 lux
Runtime	0.8-1.3/170 hrs
Beam	331 yards
Battery	1 x 18650

Optional: LED modules: WRGB, UV 365nm, UV 395nm, UV 365nm, IR 850nm, IR 940nm, Red, Green, Blue, XHP35 HI/HD.

Upgradeable LED module

- Four output levels
- Rotate head to adjust output brightness
- Tactical forward clicky switch w/ strobe

G series

Standard tactical flashlight size. Comes with 1 1/2 head diameter.

G3V NEW!

Brightness	3200 lumen
LUX@1M	15200 lux
Runtime	0.8-1.8/200 hrs
Beam	269 yards
Battery	1 x 21700

- 3200 LED lumen / 2600 ANSI FL-1 lumen, Charging and discharge battery level report
- 21700 5000mAh battery included, Deep stainless steel pocket clip
- Type-C USB rechargeable

G3L

Brightness	3200 lumen
LUX@1M	15200 lux
Runtime	0.6-1/135 hrs
Beam	269 yards
Battery	1 x 18650

- All new W2700 circuit offers maximum output, Three brightness output level setting
- Programmable medium and low brightness, Charging and discharge battery level report
- Deep stainless steel pocket clip, Includeds 10A higher discharge 18650 battery
- High current tactical switch tailcap, Type-C USB charging connection

GX30L2-R Pro MKII

Brightness	2250 lumen
LUX@1M	33500 lux
Runtime	1.4-2/300 hrs
Beam	399 yards
Battery	2 x 18650

- Professional duty light, 12V fast charging
- Five brightness levels
- 2x18650 li-ion battery pack included

GX30L2-R Diffuser

with spot output glare shield *for L.E.O.*

Brightness	1700 lumen
LUX@1M	59100 lux
Runtime	1.8/200 hrs
Beam	530 yards
Battery	2 x 18650

- New li-ion rechargeable system
- Dual switch design
- Instant strobe/MAX/MIN output

P60
Two Levels
Drop-ins

1224 LED Lumen

1900 LED Lumen

GX30A3 Diffuser

Brightness	1330 lumen
LUX@1M	51000 lux
Runtime	0.9/100 hrs
Beam	492 yards
Battery	3 x AA

*Diffuser design patented

- Built-in Spot (w/ glare shield) and Diffuser beam
- Three setting: Spot, Diffuser, Spot+Diffuser, Spot+Diffuser
- Dual switch design & five output brightness levels
- Instant MIN or MAX output

S series

Powerful output flashlight, with 1 7/8 inches head diameter.

S25V NEW!

Brightness	1200 lumen
LUX@1M	110300 lux
Runtime	2-3/250 hrs
Beam	724 yards
Battery	1 x 21700

- 724 yards (664 meters) - Osram CSLPM1 LED , Charging and discharge battery level report
- 21700 5000mAh battery included, Deep stainless steel pocket clip
- Type-C USB rechargeable

S25LR MKII

Brightness	2200 lumen
LUX@1M	44500 lux
Runtime	0.8-1.2/25 hrs
Beam	460 yards
Battery	1 x 18650

- All new W2200 circuit offers 10% higher output than the previous W1900
- Four layers FR-4 PCB, Seven large MLCC capacitors, molded power inductor
- Synchronous boots converter with ultra low resistance power mosfet
- HIgh current tactical switch tailcap, Deep stainless steel pocket clip
- Includes 10A higher discharge 18650 battery

SX30L2-R Pro MKII

Brightness	2650 lumen
LUX@1M	69300 lux
Runtime	2.1/400 hrs
Beam	574 yards
Battery	2 x 26650

- All new W2800 high output circuit
- 12V fast charging , 2x26650 li-ion battery pack included
- Professional duty light, 7.4V li-ion battery charging
- Instant strobe/MAX/MIN output

SX30L3-R Pro

Brightness	4850 lumen
LUX@1M	32500 lux
Runtime	2.2/160 hrs
Beam	393 yards
Battery	3 x 18650

- 12W fast charging, 3x18650 li-ion battery pack included
- Powerful compact flashlight, 11.1V 3.5Ah li-ion (R38)
- DC Car charger

SX30A4

Brightness	2000 lumen
LUX@1M	43200 lux
Runtime	1.2/180 hrs
Beam	453 yards
Battery	4 x AA

SX30A6 Diffuser

with spot output glare shield *for L.E.O.*

Brightness	1405 lumen
LUX@1M	68800 lux
Runtime	1.5/200 hrs
Beam	572 yards
Battery	6 x AA

SX30L2-R Diffuser

with spot output glare shield *for L.E.O.*

Brightness	1700 lumen
LUX@1M	81300 lux
Runtime	2.3-250 hrs
Beam	622 yards
Battery	2 x 26650

- New li-ion rechargeable system, Dual switch
- Instant Strobe/MAX/MIN output
- High capacity 7.4V R33 li-ion pack
- Spot and/or Diffuser output

S200C2

Brightness	1278 lumen
LUX@1M	39000 lux
Runtime	1.5/80 hrs
Beam	431 yards
Battery	1x18650 / 2xCR123A

SX30C2

Brightness	2000 lumen
LUX@1M	43200 lux
Runtime	1.3/200 hrs
Beam	453 yards
Battery	1x18650 / 2xCR123A

SX30L3 Pro

Brightness	4350 lumen
LUX@1M	28400 lux
Runtime	1.4/300 hrs
Beam	367 yards
Battery	6xCR123A / 3x18650

- Powerful compact flashlight, Dual switch design
- User 3x18650 li-ion batteries, Five output levels

M series

High output lumen flashlight, with 2 1/2 inches head diameter

MX30L2R NEW!

Brightness	4500 lumen
LUX@1M	60500 lux
Runtime	1.3-3.2/300 hrs
Beam	536 yards
Battery	2 x 32650

- Powered by CREE XHP70.2 LED
- Professional duty light, 12V fast charging
- 2x32650 li-ion battery pack included
- Five brightness levels, Dual switch operation

MX30L2C-R NEW!

Brightness	3100 lumen
LUX@1M	135000 lux
Runtime	1.3-3.3/320 hrs
Beam	801 yards
Battery	2 x 32650

- Powered by 3*Osram CSLPM1 LED
- Professional duty light, 12V fast charging
- 2x32650 li-ion battery pack included
- Five brightness levels, Dual switch operation

MX3T Pro

Brightness	4850 lumen
LUX@1M	60500 lux
Runtime	1.3/80 hrs
Beam	536 yards
Battery	3 x 18650

- 15V fast charging, 3x18650 li-ion battery pack included
- Powerful compact flashlight, R38 battery and tripod mount (Pro)

MX30L4 Compact

Brightness	4800 lumen
LUX@1M	100800 lux
Runtime	1.5/300 hrs
Beam	692 yards
Battery	4x18650 / 8xCR123A

MX30L3-Compact / Rechargeable

Brightness	6000 lumen
LUX@1M	40200 lux
Runtime	1.3/80 hrs
Beam	437 yards
Battery	38.8Wh /27.7Wh

- 15V fast charging, 3x18650 li-ion battery pack included
- Powerful compact flashlight, R38 battery

MX30L4 Extra Compact

Brightness	5136 lumen
LUX@1M	20100 lux
Runtime	1.5/300 hrs
Beam	309 yards
Battery	4x18650 / 8xCR123A

M30LC2 Pro

lumen	LUX@1M	Runtime	Battery	(Beam)
2000	50400	1.3 to 200 hrs	1-2x 18650	489 yards

Pro spec

M30LC2 Compact

Upgradeable LED module

Optional remote pressure switch

CREE XP-G2 S3

lumen	LUX@1M	Runtime	2-4x CR123A 1-2x 18650	(Beam)
1284	37200	1.8 to 200 hrs		422 yards

SPORTAC®

High performance sporting flashlights

PH10C2
Headlamp

(Beam)
250
yards

DH10C2
Headlamp

lumen	LUX@1M	Runtime	2-4x CR123A 1-2x 18650	(Beam)
1120	1100	1.5 to 200 hrs		73 yards